



Katalog-Nr. Cat.-No.									6391C			6392C		
P1	Stahl Steel < 500 N/mm ²								■ v _c = 20–40 m/min	■ v _c = 20–40 m/min				
P2	Stahl Steel 500–1000 N/mm ²								■ v _c = 20–30 m/min	■ v _c = 20–30 m/min				
P3	Stahl Steel > 1000 N/mm ²								□ v _c = 10–20 m/min	□ v _c = 10–20 m/min				
M1	Rostfreie austenitische Stähle Stainless steel austenitic								■ v _c = 10–20 m/min	■ v _c = 10–20 m/min				
M2	Rostfreie martensitische Stähle Stainless steel martensitic								□ v _c = 10–15 m/min	□ v _c = 10–15 m/min				
K1	Grauguss Grey cast iron													
K2	Sphäroguss Nodular cast iron								□ v _c = 20–30 m/min	□ v _c = 20–30 m/min				
N1	Alu- & Cu-Legierungen langspanend Alu- & Copper alloys long chipping < 5 % Si								■ v _c = 20–40 m/min	■ v _c = 20–40 m/min				
N2	Alu- & Cu-Legierungen langspanend Alu- & Copper alloys long chipping 5–10 % Si								■ v _c = 15–30 m/min	■ v _c = 15–30 m/min				
N3	Alu- & Cu-Legierungen kurzspanend Alu- & Copper alloys short chipping > 10 % Si													
N4	Graphit Graphite													
S1	Titanlegierungen mittelfest Titanium alloys medium strength < 900 N/mm ²								□ v _c = 6–15 m/min	□ v _c = 6–15 m/min				
S2	Titanlegierungen hochfest Titanium alloys high strength < 1300 N/mm ²													
H1	Hartguss und Harte Stähle Chilled steel and Hardened steel 45–55 HRC													
d ₁	P	l ₁	l ₂	l ₃	d ₂	□ h12	z		Ident No.	LMT-Code	Ident No.	LMT-Code		
mit verstärktem Zylinderschaft with reinforced straight shank														
M 2	0,4	45	8	11	2,8	2,1	3	1,85	1410595	TF-CM 02x0.40-6HX-N-1	–	–		
M 2,5	0,45	50	9	15	2,8	2,1	3	2,35	1410602	TF-CM 2.5x0.45-6HX-N-1	–	–		
M 3	0,5	56	11	18	3,5	2,7	3	2,8	1410611	TF-CM 03x0.50-6HX-N-1	–	–		
M 3,5	0,6	56	12	20	4	3	3	3,2	1410618 ¹⁾	TF-CM 3.5x0.60-6HX-N-1	–	–		
M 4	0,7	63	13	21	4,5	3,4	3	3,7	1410639	TF-CM 04x0.70-6HX-N-1	–	–		
M 5	0,8	70	15	25	6	4,9	3	4,65	1410648	TF-CM 05x0.80-6HX-N-1	–	–		
M 6	1	80	16	30	6	4,9	4	5,55	1410657	TF-CM 06x1.00-6HX-N-1	–	–		
M 7	1	80	17	30	7	5,5	4	6,55	1410659	TF-CM 07x1.00-6HX-N-1	–	–		
M 8	1,25	90	18	35	8	6,2	5	7,45	1410666	TF-CM 08x1.25-6HX-N-1	–	–		
M 10	1,5	100	20	39	10	8	5	9,3	1410675	TF-CM 10x1.50-6HX-N-1	–	–		
mit Überlaufschaft with standard straight shank														
M 12	1,75	110	24	–	9	7	6	11,2	–	–	1410684	TF-CM 12x1.75-6HX-N-1		

¹⁾ Auf Anfrage verfügbar
Available on request

■ = Hauptanwendung First choice
□ = Nebenanwendung Second choice